



OMEC NORTH AMERICA INC

ALUMINIUM - GENERAL PURPOSE MOTORS

PRODUCT FEATURES



Model Number	OMT4-80M00-2 0.37KW		
Standard	IEC 60034-1	Output	0.37 KW
Hazardous Classification	None (Safe Area)	No of Poles	2 Pole
Efficiency Class	IE3	Frame Size	80M
Number of Phases	3 Phase- Induction	Mounting Type	B3; B35, B14, B5, V1
Material of Construction	Aluminium	Enclosure Type / Cooling	TEFC-IC411
Insulation Class	Class F	Degree of Protection	IP55
Temperature Rise Class	80K (B class)	Duty Cycle	S1- Continuous Duty
Ambient Temperature	-15°C ~ 50°C	Service Factor	SF 1.15
Starting Method	DOL / WYE-DELTA	Operating Altitude	1000 masl

TECHNICAL DETAILS

Winding Connection	Y (Star)						
Frequency	50Hz			60Hz			
Rated Speed	2870 Rpm			3440 Rpm			
Voltage	380	400	415	380	400	440	460
Full Load Current [IN]	0.85 A	0.81 A	0.78 A	0.85 A	0.81 A	0.74 A	0.70 A
Locked Rotor Current [IL / IN]	13.1	13.1	13.1	13.1	13.1	13.1	13.1
Full Load Torque [TN]	1.23 Nm	1.23 Nm	1.23 Nm	1.03 Nm	1.03 Nm	1.03 Nm	1.03 Nm
Locked Rotor Torque [TL / TN]	4.7	4.7	4.7	5.6	5.6	5.6	5.6
Breakdown Torque [TB / TN]	4.7	4.7	4.7	5.6	5.6	5.6	5.6
Efficiency	50% load	78.8%	78.8%	78.8%	78.8%	78.8%	78.8%
	75% load	80.5%	80.5%	80.5%	80.5%	80.5%	80.5%
	100% load	80.7%	80.7%	80.7%	80.7%	80.7%	80.7%
Power Factor (cos φ)	50% load	0.65	0.65	0.65	0.65	0.65	0.65
	75% load	0.76	0.76	0.76	0.76	0.76	0.76
	100% load	0.82	0.82	0.82	0.82	0.82	0.82

OTHER DETAILS

Bearing Configuration (DE / NDE)	Ball Bearing / Ball Bearing			
Bearing Lubrication Type	Grease - Mobil Polyrex EM			
Bearing Series Type	DE:	6204-2Z/C3	NDE:	6204-2Z/C3
Vibration	1.6 mm/sec	Direction of Rotation	CW or CCW	
Moment of inertia (kg.m ²)	0.0011	Sound Pressure Level	67 dB(A)	
Final Colour	RAL-7031 : BLUE GREY	Paint Specification	2 Pack Epoxy	
Terminal Box Position	TOP/SIDE	Weight	10 kg	





OMEC NORTH AMERICA INC.

Performance Curves

kW: 0.37 RPM: 2870

IE3 GENERAL PURPOSE MOTORS- OMT 400V 50Hz

