



OMEC NORTH AMERICA INC

ALUMINIUM - GENERAL PURPOSE MOTORS

PRODUCT FEATURES

Model Number	OMT4-80M00-4 0.37KW		
Standard	IEC 60034-1	Output	0.37 KW
Hazardous Classification	None (Safe Area)	No of Poles	4 Pole
Efficiency Class	IE3	Frame Size	80M
Number of Phases	3 Phase- Induction	Mounting Type	B3; B35, B14, B5, V1
Material of Construction	Aluminium	Enclosure Type / Cooling	TEFC-IC411
Insulation Class	Class F	Degree of Protection	IP55
Temperature Rise Class	80K (B class)	Duty Cycle	S1- Continuous Duty
Ambient Temperature	-15°C ~ 50°C	Service Factor	SF 1.15
Starting Method	DOL / WYE-DELTA	Operating Altitude	1000 masl


TECHNICAL DETAILS

Winding Connection	Y (Star)						
Frequency	50Hz			60Hz			
Rated Speed	1425 Rpm			1710 Rpm			
Voltage	380	400	415	380	400	440	460
Full Load Current [IN]	0.93 A	0.88 A	0.85 A	0.93 A	0.88 A	0.80 A	0.77 A
Locked Rotor Current [IL / IN]	9.1	9.1	9.1	9.1	9.1	9.1	9.1
Full Load Torque [TN]	2.48 Nm	2.48 Nm	2.48 Nm	2.07 Nm	2.07 Nm	2.07 Nm	2.07 Nm
Locked Rotor Torque [TL / TN]	3.4	3.4	3.4	4.1	4.1	4.1	4.1
Breakdown Torque [TB / TN]	3.4	3.4	3.4	4.1	4.1	4.1	4.1
Efficiency	50% load	70.3%	70.3%	70.3%	70.3%	70.3%	70.3%
	75% load	80.6%	80.6%	80.6%	80.6%	80.6%	80.6%
	100% load	80.8%	80.8%	80.8%	80.8%	80.8%	80.8%
Power Factor (cos φ)	50% load	0.52	0.52	0.52	0.52	0.52	0.52
	75% load	0.67	0.67	0.67	0.67	0.67	0.67
	100% load	0.75	0.75	0.75	0.75	0.75	0.75

OTHER DETAILS

Bearing Configuration (DE / NDE)	Ball Bearing / Ball Bearing		
Bearing Lubrication Type	Grease - ESSO UNIREX N2		
Bearing Series Type	DE:	6204-2Z/C3	NDE: 6204-2Z/C3
Vibration	1.6 mm/sec	Direction of Rotation	CW or CCW
Moment of inertia (kg.m ²)	0.0028	Sound Pressure Level	58 dB(A)
Final Colour	RAL-7031 : BLUE GREY	Paint Specification	2 Pack Epoxy
Terminal Box Position	TOP/SIDE	Weight	10 kg

80-B3 Mounting diagram





OMEC NORTH AMERICA INC.

Performance Curves

kW: 0.37 RPM: 1430

IE3 GENERAL PURPOSE MOTORS- OMT 400V 50Hz

