



OMEC NORTH AMERICA INC

ALUMINIUM - GENERAL PURPOSE MOTORS

PRODUCT FEATURES


Model Number	OMT4-90L00-2 2.2KW		
Standard	IEC 60034-1	Output	2.20 KW
Hazardous Classification	None (Safe Area)	No of Poles	2 Pole
Efficiency Class	IE3	Frame Size	90L
Number of Phases	3 Phase- Induction	Mounting Type	B3; B35, B14, B5, V1
Material of Construction	Aluminium	Enclosure Type / Cooling	TEFC-IC411
Insulation Class	Class F	Degree of Protection	IP55
Temperature Rise Class	80K (B class)	Duty Cycle	S1- Continuous Duty
Ambient Temperature	-15°C ~ 50°C	Service Factor	SF 1.15
Starting Method	DOL / WYE-DELTA	Operating Altitude	1000 masl

TECHNICAL DETAILS

Winding Connection	Y (Star)						
Frequency	50Hz			60Hz			
Rated Speed	2880 Rpm			3455 Rpm			
Voltage	380	400	415	380	400	440	460
Full Load Current [IN]	4.58 A	4.35 A	4.19 A	4.58 A	4.35 A	3.95 A	3.78 A
Locked Rotor Current [IL / IN]	7.1	7.1	7.1	7.1	7.1	7.1	7.1
Full Load Torque [TN]	7.30 Nm	7.30 Nm	7.30 Nm	6.08 Nm	6.08 Nm	6.08 Nm	6.08 Nm
Locked Rotor Torque [TL / TN]	2.2	2.2	2.2	2.6	2.6	2.6	2.6
Breakdown Torque [TB / TN]	2.3	2.3	2.3	2.8	2.8	2.8	2.8
Efficiency	50% load	83.5%	83.5%	83.5%	83.5%	83.5%	83.5%
	75% load	85.8%	85.8%	85.8%	85.8%	85.8%	85.8%
	100% load	85.9%	85.9%	85.9%	85.9%	85.9%	85.9%
Power Factor (cos φ)	50% load	0.65	0.65	0.65	0.65	0.65	0.65
	75% load	0.77	0.77	0.77	0.77	0.77	0.77
	100% load	0.85	0.85	0.85	0.85	0.85	0.85

OTHER DETAILS

Bearing Configuration (DE / NDE)	Ball Bearing / Ball Bearing			
Bearing Lubrication Type	Grease - Mobil Polyrex EM			
Bearing Series Type	DE:	6205-2Z/C3	NDE:	6205-2Z/C3
Vibration	1.6 mm/sec	Direction of Rotation	CW or CCW	
Moment of inertia (kg.m ²)	0.0031	Sound Pressure Level	78 dB(A)	
Final Colour	RAL-7031 : BLUE GREY	Paint Specification	2 Pack Epoxy	
Terminal Box Position	TOP/SIDE	Weight	14 kg	





OMEC NORTH AMERICA INC.

Performance Curves

kW: 2.2 RPM: 2880

IE3 GENERAL PURPOSE MOTORS- OMT 400V 50Hz

