



OMEC NORTH AMERICA INC

CAST IRON - GENERAL PURPOSE MOTORS

PRODUCT FEATURES

Model Number	OMT3-250SM0-2 55KW		
Standard	IEC 60034-1	Output	55.00 KW
Hazardous Classification	None (Safe Area)	No of Poles	2 Pole
Efficiency Class	IE3	Frame Size	250SM
Number of Phases	3 Phase- Induction	Mounting Type	B3; B35, B5, V1
Material of Construction	Cast Iron	Enclosure Type / Cooling	TEFC-IC411
Insulation Class	Class F	Degree of Protection	IP55
Temperature Rise Class	80K (B class)	Duty Cycle	S1- Continuous Duty
Ambient Temperature	-15°C ~ 50°C	Service Factor	SF 1.15
Starting Method	DOL / WYE-DELTA	Operating Altitude	1000 masl

TECHNICAL DETAILS

Winding Connection	Δ (Delta)						
Frequency	50Hz			60Hz			
Rated Speed	2975 Rpm			3570 Rpm			
Voltage	380	400	415	380	400	440	460
Full Load Current [IN]	98.43 A	93.51 A	90.13 A	98.43 A	93.51 A	85.01 A	81.31 A
Locked Rotor Current [IL / IN]	7.7	7.7	7.7	7.7	7.7	7.7	7.7
Full Load Torque [TN]	176.55 Nm	176.55 Nm	176.55 Nm	147.13 Nm	147.13 Nm	147.13 Nm	147.13 Nm
Locked Rotor Torque [TL / TN]	2.0	2.0	2.0	2.4	2.4	2.4	2.4
Breakdown Torque [TB / TN]	2.3	2.3	2.3	2.8	2.8	2.8	2.8
Efficiency	50% load	93.3%	93.3%	93.3%	93.3%	93.3%	93.3%
	75% load	94.2%	94.2%	94.2%	94.2%	94.2%	94.2%
	100% load	94.3%	94.3%	94.3%	94.3%	94.3%	94.3%
Power Factor (cos φ)	50% load	0.82	0.82	0.82	0.82	0.82	0.82
	75% load	0.88	0.88	0.88	0.88	0.88	0.88
	100% load	0.90	0.90	0.90	0.90	0.90	0.90

OTHER DETAILS

Bearing Configuration (DE / NDE)	Ball Bearing / Ball Bearing		
Bearing Lubrication Type	Grease - Mobil Polyrex EM		
Bearing Series Type	DE:	6315/C3	NDE: 6314/C3
Vibration	2.2 mm/sec	Direction of Rotation	CW or CCW
Moment of inertia (kg.m ²)	0.4642	Sound Pressure Level	92 dB(A)
Final Colour	RAL-5012 : BLUE	Paint Specification	2 Pack Epoxy
Terminal Box Position	TOP/SIDE	Weight	390 kg



OMEC NORTH AMERICA INC.

Performance Curves

kW: 55 RPM: 2975

IE3 GENERAL PURPOSE MOTORS- OMT 400V 50Hz

