



OMEC NORTH AMERICA INC

UL LISTED VERTICAL HOLLOW SHAFT MOTORS

PRODUCT FEATURES

Model Number	-		
Standard	NEMA MG-1	Output	50HP / 37KW
Hazardous Classification	None (Safe Area)	No of Poles	2P
Efficiency Class	NEMA HIGH (IE2)	Frame Size	326TP
Number of Phases	3 Phase- Induction	Type	VERTICAL HOLLOW SHAFT
Material of Construction	Cast Iron	Enclosure Type / Cooling	WP1 / IC01
Insulation Class	Class F	Degree of Protection	IP23
Temperature Rise Class	80K (B class)	Duty Cycle	S1- Continuous Duty
Ambient Temperature	-15°C ~ 50°C	Service Factor	SF 1.15
Starting Method	PWS or YD	Operating Altitude	1000 masl & <95% RH

TECHNICAL DETAILS

Winding Connection	Δ (Delta)						
KVA Code	CODE H						
Nema Design	DES B						
Frequency	50Hz			60Hz			
Rated Speed	2950 Rpm			3550 Rpm			
Voltage	380	400	415	380	400	440	460
Full Load Current [IN]	68.00 A	64.00 A	62.00 A	68.00 A	64.00 A	59.00 A	56.00 A
Locked Rotor Current [IL / IN]	5.6	5.6	5.6	5.6	5.6	5.6	5.6
I max [Less than or Equal]	380.05 A	361.05 A	348.00 A	380.05 A	361.05 A	328.23 A	313.96 A
Starting Torque [Tst]	123%	123%	123%	123%	123%	123%	123%
Breakdown Torque [Tmax]	222%	222%	222%	222%	222%	222%	222%
Efficiency	100% load	92.4%	92.4%	92.4%	92.4%	92.4%	92.4%
Power Factor (cos φ)	100% load	0.92	0.92	0.92	0.92	0.92	0.92

OTHER DETAILS

Bearing Configuration (DE / NDE)	Angular Contact Ball Bearing/Guide Ball Bearing		
Bearing Lubrication Type	DE:	ISO-32 Oil	NDE: Grease
Bearing Series Type	DE:	7024BD/DT	NDE: 6213/C3
Coupling Size	As per Drawings	Direction of Rotation	CW from DE
Final Colour	RAL 3002- RED	Paint Specification	2 Pack Epoxy
Downthrust	3500 LBS	Mounting Option	P-BASE



VERTICAL HOLLOW SHAFT MOTORS WEATHER PROTECTED TYPE 1

OMEC NORTH AMERICA INC

50HP(326TP)

Model No.	Frame	Mounting Dimensions(inch)												Overall Dimensions(inch)			Bearings			Weight (L/B)
		BD	AJ	AK	BV	AF	BF	BX	BZ	EW	BY	CD	EO>	P	AB	AC	AG	Drive End	Opposite DriveEnd	
50HP	326TP	16.5	14.75	13.5	13.78	4	0.69	1.25	1.75	0.25	1/4-20	28.22	4	17.32	15.1	11.08	32.52	7024BDT	6213	760

Model No.	Frame	Mounting Dimensions(inch)							
		BX				BD			
50HP	326TP	1	1.188	1.25				16.5	

